





















- **▶** WELLMATE
 - ▶ PRO-SOURCE
- **► MYERS**
- ► INTELLIFLO
- ► FLOTEC
- ▶ WHISPERFLO ▶ STA-RITE



PENTAIR POOL

INTELLIFLO i1 AND i2 VARIABLE SPEED PUMP



- Permanent magnet motor runs cooler, produces less vibration than induction motors
- Totally enclosed fan-cooled (TEFC) design protects against the elements
- Heavy-duty/durable construction is designed for long life

PART# DESCRIPTION

VOLT. AMPS HP ORDER

011059 IntelliFlo i1 Variable Speed Pump 230V 7.3 1 1 011060 IntelliFlo i2 Variable Speed Pump 230V 11.8 2 1





- Modular plumbing system means less need to cut and glue pipe
- External port threading and tool-free union nuts need only hand-tightening
- Easy-carry handle; easily removable, ergonomic lock ring; and see-through lid for easy basket inspection

| | | | | | UNIT |
|--------|--|-----------|-----------|----|-------|
| PART# | DESCRIPTION | VOLT. | AMPS | HP | ORDER |
| 022009 | XFE-8 WhisperFloXF Efficient Single Speed Full Rated Pump | 208V-230V | | | 1 |
| 022010 | XFE-12 WhisperFloXF Efficient Single Speed Full Rated Pump | 208V-230V | 15.0-13.6 | 3 | 1 |



PENTAIRPOOL

TRITON II FIBERGLASS SAND FILTER



- Heavy-duty closure provides easy inspection
- Easy-to-read pressure gauge with air relief valve
- Instant access to sand and all internal parts
- Internal air bleed automatically prevents unwanted air pockets
- Combination sand and water drain makes servicing and winterizing fast and easy



| PART# | A. DIM. | B. DIM. | C. DIM. | D. DIM. |
|--------|----------|---------|---------|---------|
| 140236 | 30-1/2" | 19-1/2" | 10-3/4" | 32-1/2" |
| 140249 | 34-3/4" | 21-1/2" | 11-7/8" | 36-3/4" |
| 140264 | 35- 1/2" | 24-1/2" | 13-5/8" | 37-1/2" |
| 140210 | 39-3/4" | 30-1/2" | 16-1/4" | 41-3/4" |
| 140243 | 45-1/4" | 36-1/2" | 18-3/4" | 47-1/4" |
| | | | | |





- Heavy-Duty Cast Iron
 Construction
- Superior Performance at Depths-to-Water of 25' of Less
- Pre-Wired Pressure Switch
- Dual Voltage Motor Can Run on 115V or 230V (factory preset to 115V)

| | | UNIT | |
|--------|------------------|-------|------|
| PART# | DESCRIPTION | ORDER | PACK |
| FP4155 | 1/2 HP 115V/230V | 1 | вох |
| FP4157 | 3/4 HP 115V/230V | 1 | BOX |
| FP4150 | 1 HP 115V/230V | 1 | BOX |





- Superior performance at dephts to water of 25' or less with maximum pumping capacities to 5 GPM
- Fiberglass-reinforced thermoplastic pump housing for corrosion resistance
- Ready-to-install 230 volt motor Conversion ability to 115V
- 1-1/4" NPT suction and 3/4" NPT discharge pipe sizes

| | | UNII | |
|--------|------------------|-------|------|
| PART# | DESCRIPTION | ORDER | PACK |
| FP4012 | 1/2 HP 115V/230V | 1 | вох |
| FP4022 | 3/4 HP 115V/230V | 1 | вох |
| FP4032 | 1 HP 115V/230V | 1 | BOX |





- Quality Construction Close-grained cast iron body. Drain port provided for easy winterizing
- Precision Molded Diffuser Pump primes faster, handles more air, with multi-port, precision-molded, reinforced polypropylene diffuser
- Heavy-duty Ball Bearings Shielded, permanently lubricated bearings, extensively tested to ensure extended life and smooth quiet operation

| | | UNIT | |
|-------|------------------|-------|------|
| PART# | DESCRIPTION | ORDER | PACK |
| SNC-L | 1/2 HP 115V/230V | 1 | вох |
| SND-L | 3/4 HP 115V/230V | 1 | BOX |
| SNE-L | 1 HP 115V/230V | 1 | вох |
| SNF-L | 1.5 HP 115V/230V | 1 | BOX |



PENTAIR

STA-RITE CJ SERIES SHALLOW WELL JET PUMP (STAINLESS STEEL)



- Corrosion Free Stainless steel pump body provides maximum resistance to corrosion
- Built-in Jet High strength thermoplastic components are corrosion resistant
- Mechanical Shaft Seal -Highly polished carbon-ceramic and stainless steel construction
- Motor Windings Superior insulation materials protect against excessive moisture and contaminants --assure prolonged motor life

| | | UNII | |
|-------|--------------------|-------|------|
| PART# | DESCRIPTION | ORDER | PACK |
| CJ90E | 1 HP 115V/230V | 1 | вох |
| CJ90F | 1-1/2 HP 115V/230V | 1 | вох |





- Cast Iron Pump Case
- Dual Compartment, 115/230V Double-Ball Bearing Motor With Voltage Selector Switch -Priming Screen
- Diffuser With Stainless Steel Wear Ring
- Square D Pressure Switch

| | | UNIT | |
|--------|------------------|-------|------|
| PART# | DESCRIPTION | ORDER | PACK |
| HR50S | 1/2 HP 115V/230V | 1 | вох |
| HJ75S | 3/4 HP 115V/230V | 1 | вох |
| HJ100S | 1 HP 115V/230V | 1 | BOX |



PENTAIR

SUBMERSIBLE SIGNATURE 2000 PUMP (STAINLESS STEEL)



- Stainless Steel Shell, discharge bowl, shaft and coupling, wear ring and suction screen – all lead-free
- Gritty Performance Self-lubricating impellers resist abrasion from grit and sand Teflon® impregnated staging proven to outlast the competition
- Supreme Power Features the highthrust Pentek XE motor for the ultimate in power, efficient performance and longer life. Thermal overload and lightning protected
- On the Job Field serviceable, threaded pump assembly
- An Eye for Safety Built-in eyelet for safety line connection
- Control boxes available if needed for all pumps below



| | | | | UNII | |
|-------------|---------|-----------|-------------------|-------|------|
| PART# | | DESCRI | PTION | ORDER | PACK |
| 2ST51-12PLU | JS-P4 | 2-Wire Pu | ımp 115V 1/2 HP | 1 | вох |
| 2ST52-12PLU | JS-P4 | 2-Wire Pu | ımp 230V 1/2 HP | 1 | BOX |
| 2ST72-12PLU | JS-P4-2 | 2-Wire Pu | ımp 230V 3/4 HP | 1 | BOX |
| 2ST102-12PL | US-P4-2 | 2-Wire Pu | ımp 230V 1 HP | 1 | BOX |
| 3ST51-12PLU | JS-P4 | 3-Wire Pu | ımp 115V 1/2 HP | 1 | BOX |
| 3ST52-12PLU | JS-P4 | 3-Wire Pu | ımp 230V 1/2 HP | 1 | BOX |
| 3ST72-12PLU | JS-P4 | 3-Wire Pu | ımp 230V 3/4 HP | 1 | BOX |
| 3ST102-12PL | US-P4 | 3-Wire Pu | ımp 230V 1 HP | 1 | BOX |
| 3ST152-12PL | US-P4 | 3-Wire Pu | ımp 230V 1-1/2 HF | P 1 | BOX |

PENTAIR WELLMATE FIBERGLASS TANK





| | | UNIT |
|-------|-------------|-------|
| PART# | DESCRIPTION | ORDEF |
| WM4 | 15 Gallon | 1 |
| WM6 | 20 Gallon | 1 |
| WM9 | 30 Gallon | 1 |
| WM12 | 40 Gallon | 1 |
| WM14 | 47 Gallon | 1 |
| WM20 | 60 Gallon | 1 |
| WM23 | 80 Gallon | 1 |
| WM25 | 87 Gallon | 1 |
| WM35 | 120 Gallon | 1 |
| WM60 | 187 Gallon | 1 |
| WM80 | 264 Gallon | 1 |

- Durable interior air cell is fully replaceable and constructed of heavy-gauge engineered polymer
- One piece, seamless inner shell molded of premium, high-density polyethylene
- Outer shell is a composite of continuous fiberglass strands sealed with high-grade epoxy resin
- Sturdy, molded polymeric base is corrosion and impact proof
- Bottom inlet/cutlet one-piece drain is custom molded of high-impact PVC



PENTAIR

PRO-SOURCE STEEL PRESSURE TANK





| PART# | DESCRIPTION | UNIT ORDE |
|------------|-------------------------|--------------|
| PS6-S02 | Vertical 6 Gallon | 1 |
| PS19S-T02 | Vertical "Short" 19 Gal | 1 |
| PS19T-T02 | Vertical 19 Gallon | 1 |
| PS32-T03 | Vertical 32 Gallon | 1 |
| PS35-T05 | Vertical 35 Gallon | 1 |
| PS50-T50 | Vertical 50 Gallon | 1 |
| PS62-T51 | Vertical 62 Gallon | 1 |
| PS85-T52 | Vertical 85 Gallon | 1 |
| PS119-TR50 | Vertical 119 Gallon | 1 |
| PS6H-S05 | Horizontal 6 Gallon | 1 |
| PS19H-S00 | Horizontal 19 Gallon | 1 |
| | | |

- Maximum Operating Pressure: 100 PSI on 16" and 20" tanks; 125 PSI on 24" tanks
- Heavy-Gauge Metal Construction: Sturdy "welded wrapper and head design." Built to last
- Polyester Paint Finish: Electrostatically powder-painted, then oven-baked for a smooth high-gloss, appliance quality finish
- NEW Stainless Service Connection: Stainless steel corrosion resistant



954.327.2478 | sales@dacoworld.com w w w . d a c o w o r l d . c o m